


SUMMIT | ASCENT-r™

GROUND-MOUNTED OR INVERTED RUNNING MAN.



Ground-mounted or inverted configuration.



Varying speed modes.
Walk, Jog, or Run.



Engineered durable to
withstand daily abuse.



Rated for all weather conditions
and climates.



Individual control, or synchronized
with a master control.



Minimal power consumption.



Quiet and quick operation.



Slim profile allows for easy
installation and upgrade.



Smooth thanks to our innovative multi-
wheel and cable design.

SUMMIT | ASCENT-r™

⊕ **CLOSE-LOOP, INTEGRATED DRIVE, BRUSHLESS MOTOR**
-840 oz-in of torque
-anti-slip design with pinpoint accuracy

⊕ **INVERTABLE DESIGN**
Designed to be mounted to
the ground or ceiling

SMOOTH GLIDE WHEELS
-durable

CABLE DRIVEN
-long life cable design
-protected for maximum cable life
-easy access for quick replacement



⊕

⊕ **ALL-WEATHER RATED**
Fully protected control lines

⊕ **MODULAR TRACK**
11 gauge pre-galvanized finish
adapts to any range size



LATERAL RUNNERS BREAKDOWN

	SUMMIT RIDGE-360r™ WIRELESS RUNNER	SUMMIT RIDGE-r™ WIRELESS RUNNER	SUMMIT ASCENT-r™ CABLE-DRIVEN RUNNER
 TURNING MODES	90° 180° 360°	N/A	N/A
 POWER SOURCE	WIRELESS BATTERY-POWERED 100-240 VAC	WIRELESS BATTERY-POWERED 100-240 VAC	CABLE-DRIVEN 100-240 VAC
 CONTROL METHODS	*MASTER TOUCH PAD LOCAL TOUCH PADS	*MASTER TOUCH PAD LOCAL TOUCH PADS	MASTER TOUCH PAD *LOCAL TOUCH PADS *REMOTE CONTROL FOB
 SPEED	UP TO 0.4 sec 90° TURNING WALK / JOG / RUN MAX: 12 ft/s	WALK / JOG / RUN MAX: 12 ft/s	WALK / JOG / RUN MAX: 12 ft/s
 BUILT-IN PROGRAMS	N/A	N/A	N/A
 ORIENTATION	CEILING MOUNTED	CEILING MOUNTED	CEILING / GROUND MOUNTED
 ADDITIONAL FEATURES	MULTIPLE CLAMP STYLES	MULTIPLE CLAMP STYLES	OUTDOOR RATED MULTIPLE CLAMP STYLES
 DISTANCE	UP TO 110 yd *OR MORE	UP TO 110 yd *OR MORE	UP TO 50 yd

*Optional Feature