


SUMMIT | PEAK-360i™

INVERTED, ELECTRIC-DRIVEN TARGET TURNER.



Baffle-protected, inverted configuration.



90, 180, and 360° turning with friend / foe presentation.



AR500 ballistic shield protection.



Individual control, or synchronized with a master control.



Engineered durable to withstand daily abuse.



Minimal power consumption.



Rated for all weather conditions and climates.



Quiet and quick operation.



Maximum range up-time with bus communications.



ROBUST MOTOR DRIVE UNIT
Geared servo w/ integrated drive
2500 oz-in of torque

⊕ **OPTIONAL LED TACTICAL LIGHTING**
Flashing red / blue distraction

⊕ **OPTIONAL ALL-WEATHER RATED**
Fully protected control lines

⊕ **BUS COMMUNICATIONS**
If a target fails, it will not affect the
operation of other targets

AR500
Downrigger
Various lengths available


TURNING
90°, 180°, 360°

AR500
Clamp
Various configurations available

SUMMIT | **PEAK-360i™**



TURNERS BREAKDOWN

	SUMMIT PEAK-360i™ CEILING-MOUNTED TURNER	SUMMIT PEAK-i™ CEILING-MOUNTED TARGET HOLDER	SUMMIT PEAK-360™ GROUND-MOUNTED TURNER	SUMMIT PEAK™ GROUND-MOUNTED TARGET HOLDER
 TURNING MODES	90° 180° 360°	MANUAL 90° 180° 360°	90° 180° 360°	MANUAL 90° 180° 360°
 POWER SOURCE	ELECTRIC 100-240 VAC	N/A	ELECTRIC 100-240 VAC	N/A
 CONTROL METHODS	MASTER TOUCH PAD *LOCAL TOUCH PADS *REMOTE CONTROL FOB	N/A	MASTER TOUCH PAD *LOCAL TOUCH PADS *REMOTE CONTROL FOB	N/A
 SPEED FEET/SEC	UP TO 0.4 sec 90° TURNING	N/A	UP TO 0.4 sec 90° TURNING	N/A
 BUILT-IN PROGRAMS	QUALIFICATION COURSES OF FIRE	N/A	QUALIFICATION COURSES OF FIRE	N/A
 BALLISTIC RATING	AR500 1/4 in *3/8 in	AR500 1/4 in *3/8 in	AR500 1/4 in *3/8 in	AR500 1/4 in *3/8 in
 ADDITIONAL FEATURES	*OUTDOOR RATED *TACTICAL LIGHTING *LATERAL REPOSITIONING MULTIPLE CLAMP STYLES	OUTDOOR RATED *LATERAL REPOSITIONING MULTIPLE CLAMP STYLES	OUTDOOR RATED *TACTICAL LIGHTING *KNEEWALL OPTIONAL MULTIPLE CLAMP STYLES	OUTDOOR RATED *KNEEWALL OPTIONAL MULTIPLE CLAMP STYLES

*Optional Feature